


Controlling Thermal Effects in DoD Inkjet Printhead

Amritam Das

Control Systems Group, Eindhoven University of Technology






Inkjet Printing



Ink is jetted on the substrate medium in a **predefined** pattern

Inkjet Printing

Ink is jetted on the substrate medium in a **predefined** pattern









Requirements


- High quality
- High throughput
- Less cost



(a) Too small droplet volume




(b) Favorable droplet volume




(c) Too large droplet volume

Requirements


- High quality
- High throughput
- Less cost



(d) Too small
droplet volume



(e) Favorable
droplet volume




(f) Too large
droplet volume

Temperature consistency is vital !

Thermo-Fluidic Process

Interaction of solids and fluids under influence of Thermal Input



Develop a virtual prototyping tool for controlling thermo-fluidic aspects in inkjet printhead.


- Thermo-fluidic model should be modular and adjustable.
- No additional actuator or sensor is allowed to use.

Develop a virtual prototyping tool for controlling thermo-fluidic aspects in inkjet printhead.

- Thermo-fluidic model should be modular and adjustable.
- No additional actuator or sensor is allowed to use.

Develop a virtual prototyping tool for controlling thermo-fluidic aspects in inkjet printhead.

- Thermo-fluidic model should be modular and adjustable.
- No additional actuator or sensor is allowed to use.




Thermo-Fluidic Process

The interaction of solids and liquids under influence of thermal dissipation.

Thermal Heat transfer

- Conduction
- Convection
- Advection



1 The finite graph $\mathcal{G}(\mathcal{N}(\Theta), \mathcal{E})$

2 The set of nodes $\mathcal{N}(\Theta) := \{\mathcal{N}_1(\Theta), \dots, \mathcal{N}_{nn}(\Theta)\}$


3 The Adjacent matrix $\mathcal{A} \in \mathbb{Z}^{nn \times nn}$


$$\mathcal{A}_{i,j} = \begin{cases} 1, & \text{iff } \mathcal{N}_i(\Theta) \text{ has a connection with } \mathcal{N}_j(\Theta) \\ 0, & \text{otherwise} \end{cases}$$


4 The set of edges $\mathcal{E}$ In particular,

$$\mathcal{E} := \{\mathcal{E}_{i,j} \mid \forall \mathcal{A}_{i,j} = 1\}, \text{ with}$$


$$\mathcal{E}_{i,j} := \{w_{i,j} = v_{j,i} \mid \mathcal{A}_{i,j} = 1, i \neq j\}$$












$$\begin{bmatrix} \dot{x}_i(t) \\ w(t) \\ q_i(t) \\ y_i(t) \end{bmatrix} = \underbrace{\begin{bmatrix} A_{xx}^i & B_{xv}^i & B_{xp}^i & B_{xu}^i & B_{xd}^i \\ C_{wx}^i & D_{wv}^i & D_{wp}^i & D_{wu}^i & D_{wd}^i \\ C_{qx}^i & D_{qv}^i & D_{qp}^i & D_{qu}^i & D_{qd}^i \\ C_{yx}^i & D_{yv}^i & D_{yp}^i & D_{yu}^i & D_{yd}^i \end{bmatrix}}_{\mathcal{P}_i} \begin{bmatrix} x_i(t) \\ v(t) \\ p_i(t) \\ u_i(t) \\ d_i(t) \end{bmatrix}$$






The model can be extended to arbitrary number of nozzles





$$y(t) = \alpha(e^{-\zeta} \sin(\omega t + \phi)) + \gamma$$

- $\alpha \Rightarrow$ Amplitude [V]
- $\zeta \Rightarrow$ Damping [-]
- $\omega \Rightarrow$ Frequency [rad/s]
- $\phi \Rightarrow$ Phase shift [rad]
- $\gamma \Rightarrow$ Offset [V]
- $\varphi \Rightarrow$ Energy [J]



$$y(t) = \alpha(e^{-\zeta} \sin(\omega t + \phi)) + \gamma$$

- $\alpha \Rightarrow$ Amplitude [V]
- $\zeta \Rightarrow$ Damping [-]
- $\omega \Rightarrow$ Frequency [rad/s]
- $\phi \Rightarrow$ Phase shift [rad]
- $\gamma \Rightarrow$ Offset [V]
- $\varphi \Rightarrow$ Energy [J]

Use the key parameters to estimate temperature

Prametrizing Output response

$$y(k) = e^{Ak}x(0) = Z^k x(0)$$

$$Z = \overleftarrow{Y}^\dagger Y;$$


Construct the Hnakel matrix

$$Y = \begin{bmatrix} y_0 & \cdots & y_{L-2} & y_{L-1} \\ y_1 & \cdots & y_{L-1} & y_L \\ \vdots & \ddots & \vdots & \vdots \\ y_{N-L-1} & \cdots & y_{N-3} & y_{N-2} \end{bmatrix}, \quad \overleftarrow{Y} = \begin{bmatrix} y_1 & \cdots & y_{L-1} & y_L \\ y_2 & \cdots & y_L & y_{L+2} \\ \vdots & \ddots & \vdots & \vdots \\ y_{N-L} & \cdots & y_{N-2} & y_{N-1} \end{bmatrix}$$


Find SVD of Z

$$Z = \overleftarrow{Y}^\dagger Y = \left[\sum_{k=1}^{2K} \frac{1}{\sigma_k} v_k u_k^\top \right] Y$$


Find the Poles $p = \ln\{\sigma(Z)\}$



Step 2: Use energy of the output response to estimate temperature **TU/e**



Evaporation Effect






Figure: Variance plot of calibration III with 2000 jetting pulses




Figure: Temperature/energy curves of multiple nozzles




Figure: Variance plot of calibration III with 2000 jetting pulses




Figure: Temperature/energy curves of multiple nozzles

The soft sensor is accurate within 0.1 degree

Controller Requirement

Need to **anticipate** and **compensate** the temperature changes

Controller's Job

- ① Utilise prior information of print-profile
- ② Respect the constraints on states and inputs

Use the piezo as an heating actuator while no jetting

Controller Requirement

Need to **anticipate** and **compensate** the temperature changes

Controller's Job

- ① Utilise prior information of print-profile
- ② Respect the constraints on states and inputs

Use the piezo as an heating actuator while no jetting

Prediction
Model


Controller Requirement

Need to **anticipate** and **compensate** the temperature changes

Controller's Job

- ① Utilise prior information of print-profile
- ② Respect the constraints on states and inputs

Use the piezo as an heating actuator while no jetting




Controller Requirement

Need to **anticipate** and **compensate** the temperature changes

Controller's Job

- ① Utilise prior information of print-profile
- ② Respect the constraints on states and inputs

Use the piezo as an heating actuator while no jetting



Controller Requirement


Need to **anticipate** and **compensate** the temperature changes

Controller's Job

- ① Utilise prior information of print-profile
- ② Respect the constraints on states and inputs

Use the piezo as an heating actuator while no jetting

MPC CONTROLLER



- **Prediction model** In discrete time

$$x_{i+1|k} = A_{i|k}x_{i|k} + B_{i|k}u_{i|k} + f_{i|k}, \quad \forall i = 0, 1, \dots, N-1$$

- **Prediction model** In discrete time

$$x_{i+1|k} = A_{i|k}x_{i|k} + B_{i|k}u_{i|k} + f_{i|k}, \quad \forall i = 0, 1, \dots, N-1$$


- **Optimization Problem:** Minimising the output and reference temperature

$$\|x_{N|k} - x_{N|k}^{ss}\|_{P_k}^2 + \sum_{i=0}^{N-1} \|x_{i|k} - x_{i|k}^{ss}\|_Q^2 + \|u_{i|k} - u_{i|k}^{ss}\|_R^2$$

subject to

$$u_{min} \leq u_{i|k} \leq u_{max};$$

$$x_{min} \leq x_{i|k} \leq x_{max}, \quad i = 0, \dots, N$$




- ❶ The finite graph $\mathcal{G}(\mathcal{N}(\Theta), \mathcal{E})$
- ❷ The set of nodes $\mathcal{N}(\Theta) := \{\mathcal{N}_1(\Theta), \dots, \mathcal{N}_{nn}(\Theta)\}$
- ❸ The Adjacent matrix $\mathcal{A} \in \mathbb{Z}^{nn \times nn}$

$$\mathcal{A}_{i,j} = \begin{cases} 1, & \text{iff } \mathcal{N}_i(\Theta) \text{ has a connection with } \mathcal{N}_j(\Theta) \\ 0, & \text{otherwise} \end{cases}$$
- ❹ The set of edges $\mathcal{E}$ In particular,

$$\mathcal{E} := \{\mathcal{E}_{i,j} \mid \forall \mathcal{A}_{i,j} = 1\}, \text{ with}$$

$$\mathcal{E}_{i,j} := \{w_{i,j} = v_{j,i} \mid \mathcal{A}_{i,j} = 1, i \neq j\}$$



System-Level Thinking for Model-Based Control of Large Scale Models

Conclusion

- A modular, completely flexible modeling framework for thermal aspects in printhead.
- Fully automated software tools for simulation, design optimization and controller synthesis.
- Exploiting piezo as a self-sensing actuator; no need of additional sensors and heaters.

Future work

- Designing non-jetting pulse to generate control input for heating.
- Improve scalability of controller for implementation.
- Investigate new control architectures.

Thank You!